

# HURCO WINCH SYSTEM SPECIFICATIONS

- High efficient Planetary winch capable of up to 20,000 pounds of line pull.
  - Multi-Disc Wet Brakes
  - Spring-Applied/Hydraulic Brake release
  - Fast line speeds under load
  - Hydraulic Brake valve
  - Right and Left hand drum rotations
  - 600' 3/8 inch all steel cable with braded end loop
  
- Hatz 2L41C Diesel Engine with Silent Pack feature 35HP
  - Air cooled engine
  - Cast Iron crankcase, vertical in-line cylinders
  - Extremely low fuel and oil consumption
  - The most silent industrial Diesel engine in its class
  - Silent Pack enclosure reduces the engine noise by 90%
  - Integrated exhaust silencer
  
- Electric winch boom assembly for lowering equipment in and out of manhole.
  - 1500 lb capacity
  - Remote wired control
  
- 1/4 inch rope mounted rope reel for deflection testing after re-rounding. When the re-rounder is pulled through the pipe, a trailing rope is disconnected from the re-rounder and attached to a deflection gauge. The other end of the deflection gauge is connected with the rope from this rope reel.
  
- Hydraulic outriggers.
  - Fold up for travel.
  - Can be used to help inch a re-rounder in a tight pull
  
- Pneumatic safety release control levers.
- High leverage hand controlled level wind for winch drum.
- 10 gallon fuel tank
- 20 gallon hydraulic tank
- Heavy duty Cross Roller Guide
- Heavy duty uni-body trailer design
- Heavy duty axel with electric brakes
- Trailer light package
- Aluminum Tool Box mounted on front of trailer (Not Pictured) 17" tall x 20" wide x 36" long.