



SDT-800 SPECIFICATIONS

TRAILER:

- OAL = 9'-5" trailer, (11'-3" with SD-800 Boom mounted)
- OAW = 6'-0"
- OAH = 48" trailer, (6'-9" with SD-800 Boom & Strobe light)
- GVW = 1600 lbs.
- Tongue weight = 150 lbs.
- Trailer lights with Flat-four trailer connector.
- Side marker lights & reflective tape
- Wrench holder
- Spin Doctor head rest for travel position.
- Aluminum plate tool box with gas spring lift.
- Minimum 13HP hydraulic power pack
- Auxillary 12 Volt power connection mounted at rear of trailer.

FRAME CONSTRUCTION:

- Constructed of High carbon structural steel for durability.
- Trailer bed is formed 7 ga. Steel with reinforced stress points.
- Powder Coated Gloss Black frame and fenders.
- Hitch size = 2" ball – 2000 lb GTW rated.
- Pivoting, single wheel jack stand.
- Hitch height = 13"
- Tie-down loops for transport.
- 2" x 3" x 3/16" Tongue tube with "A" bracing.

AXLE/WHEELS:

- 1600 lb rated.
- Torsion type, Rubber mounted – 45 deg. down rake
- Hub – 5 lug on 4 ½" centers
- Wheels – Steel white spoke
- Tires = 195R/13